IP Link® Device Interface
Ethernet Communication Sheet

This document provides additional assistance with wiring your Extron IP Link enabled product to your device. Different components may require a different wiring scheme than those listed below.

For complete operating instructions, refer to the user's manual for the specific Extron IP Link enabled product or the controlled device manufacturer supplied documentation.

Device Specifications:

Device Type:	Video Projector
Manufacturer:	ViewSonic
Firmware Version:	N/A
Model(s):	PJD5126, PJD5226, PJD5226W, PJD6223, PJD6253, PJD6353, PJD6353s, PJD6383, PJD6383s, PJD6553w, PJD6653W, PJD6653ws, PJD6683W, PJD6683ws

Minimum Software and Firmware Requirements:

IP Link Compiler	IP Link Firmware	GC Version
1.6.0	1.17	3.5.2

Version History:

Driver Version	Date	Notes
1	3/31/2014	Initial version.

Driver Notes:

Control Commands & States:

Aspect Ratio	Auto 16:10	4:3	16:9
Audio Mute	On	Off	
Auto Image	Execute		
Freeze	On	Off	
Input	VGA 1 S-Video	VGA 2 HDMI	Composite
Lamp Mode	Normal	Eco	
Power Control	On	Off	
Video Mute	On	Off	
Volume (Step)	Up	Down	

Status Available:

Aspect Ratio	Auto 16:10	4:3	16:9
Audio Mute	On	Off	
Connection Status	Connected	Disconnected	
Freeze	On	Off	
Input	VGA 1 S-Video	VGA 2 HDMI	Composite
Lamp Mode	Normal	Eco	
Lamp Usage	Hours		
Power Control	On	Off	
Power Status	On	Off	Status Unavailable
Video Mute	On	Off	

Network communication:

When configuring the Ethernet driver, be sure device settings match that of the GC configuration.

Port Type:	Ethernet
Logon Credentials Supported:	Undetermined
Default Port:	4661
Multi-Connection Capable:	No
Port Changeable:	No

Ethernet Driver Configuration Description:

Please refer to user manual for settings and changes to the network communication parameters such as Port Number.

Notes for the Device: